



HOSHIZAKI














	ITEM	Hoshizaki Undercounter Freezer
	MODEL	FT-186MA-T
Ą	POWER SUPPLY	1 Phase 220V ~ 60Hz Capacity: 1.20kVA (5.45A)
	AMPERAGE	Rated 2.70A
ı	ELECTRIC CONSUMPTION	Motor 400W Heater 397W
-		Refrigeration 357W Defrost 397W
ŀ	HEAT REJECTION	*W
	POWER CORD	2.0m (Plug with Earth Wire)
	EFFECTIVE CAPACITY	401L
	OUTSIDE DIMENSIONS	1800mm (W) x 600mm (D) x 800(790-820)mm (H)
	INSIDE DIMENSIONS	1440mm (W) x 436mm (D) x 599mm (H)
	EXTERIOR	Stainless Steel, Galvanized Steel (Rear / Bottom) ABS Plastic (Top & Bottom on Door)
	INTERIOR	Stainless Steel, ABS Plastic (Door)
	INSULATION	Polyurethane Foam
	INSULATION FOAM BLOWING AGENT	Cyclopentane
	REFRIGERATION SYSTEM	Forced Air Circulation
	DEFROST SYSTEM	Glass Tube Heater
	COMPRESSOR	Hermetic
	CONDENSER	Fin and Tube type, Air—cooled
	EVAPORATOR	Fin and Tube Type
	REFRIGERANT	R404A
	TEMPERATURE CONTROL	Microprocessor controlled Adjustable from −23 to −7°C
	DEFROST CONTROL	Microprocessor controlled
	ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
	COMPRESSOR PROTECTION	Motor Protector
	LEG	Plastic Adjustable 90 to 120mm
	SHELF	6pcs.
	WEIGHT	Net: 93kg (Gross: Approx. 98kg)
	PACKAGE	Carton 1865mm (W) x 680mm (D) x 790mm (H)
	ACCESSORIES	_
	OPERATING CONDITIONS	Ambient Temperature: 5-43°C Voltage Range: Rated Voltage±6%
-	*We reserve the right t	o make changes in specifications and design without prior notice.

- 1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
- 2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 35°C and power supply of 230V 50Hz. The amperage and electric consumption are based on measurements at ambient temperature of 38°C
- and power supply of 230V 50Hz.

 3. The cabinet temperature range of -23 to -7°C is guaranteed at ambient temperature of 35°C.

 4. Product code: T274-C200 (HTW)